

Pall PCM400

| Selection | Value |
|------------------|------------------|
| ID number | |
| Ex Sone | |
| Max Gross weight | 5kg |
| Surgical fluid | Water / Glycol |
| Voltage | 240 V AC |
| Type | PCM500 |
| Viscosity | 1.5 cSt> 450 cSt |



This rental product requires annual calibration

The PCM400 Fluid Cleanliness Monitor is a portable diagnostic monitoring device that provides a measurement of the system fluid unit.

Pallet PCM400 uses proven mesh technology to report accurate, reliable, 3-part ISO 4406 purity codes for most types of liquids, in many types of environments.

With PCM400 you can:

- Monitor contamination levels in mineral, synthetic or water-based liquids. The results are not affected by the presence of water, air or dark liquids
- Get accurate, 3-part * ISO 4406 cleanliness code results in less than 6 minutes and take preventative measures quickly

🇬🇧
English
>

- Upload real-time results directly to mobile devices for analysis and action
- 'Pass off' cleanliness of new buildings quickly and safely
- Protect your systems from catastrophic failures by detecting abnormal fluid cleaning conditions quickly

The PCM400 can be permanently installed to monitor critical applications (including component testing systems) or used as a portable device for routine condition monitoring of various fluid systems

Additional information:

Do not find what you are looking for - Call for assistance +47 56 12 67 00



English

